



CC200 Refrigerant Charging Scale

ACCURATE. PRECISE. RELIABLE.

The most trusted brand of refrigerant charging scales.

FEATURES:

- Weigh, charge or recover refrigerants up to 220 lb (100 kg)
- 0.2 Oz (5 g) display resolution
- Up to 30 continuous hours of battery life on one 9V battery
- Hand held corded control with large, high contrast, wide angle display
- Fully manual, 3 button keypad
- Sealed strain gauge beam load cell
- Cast aluminum platform and base for stability and weight accuracy
- · Indoor/outdoor use
- Automatic power off after 15 minutes
- 1 year warranty



Weigh, charge or recover refrigerants up to 220 lb (100 kg)



360 Swivel hanger hook



Durable molded carrying case







Warranty

Maximum Load	220 lb (100 Kg)
Weight Accuracy	\pm 0.1% Of Reading [or 0.2 Oz (5 g), whichever is greater
Display Resolution (Increments)	0.20 Oz (5 g)
Continuous Battery Life	Up To 30 Hrs (One 9V Alkaline); Up To 60 Hrs (If 2nd 9V Installed)
Platform Dimensions	9" x 9" (23 cm x 23 cm)
Control Type	Handheld LCD Display
Keypad	3 Button (On/Off, Lb/Kg, Tare)
Control to Scale Connection	4' (1.2 m) Flexcord, Extended
Maximum Tank Footring Diameter	11.5" (29.2 cm)
Auto Power Off Feature (ENABLED)	Display Turns OFF After 15 Minutes Inactivity (& No Weight On Platform)
Power Source	(1 or 2) 9V Alkaline (1 Included)
Unit Weight	7.43 Lb (With Case); 4.90 lb Scale Only
Weight Readout	Selectable (lb & oz, or kg & g)
360 Degree Hanger Hook	Yes
Packaging	4 Color Box
Quick Start Guide (4 Langauge)	Located Inside Lid (+ Connection Diagrams, Specifications)
Rubber Platform Cover	Yes
Carry Case	Molded Plastic
Overload Protection	Visual
Battery Level Indicator	3 Segment Symbol
Operating Temperature Range	32°F to 113°F (0°C to 45°C)
Approvals	CE (Commonwealth Europe)
Calibration	To National Institute Of Standards & Technology (U.S.)

1 Year



